



Touch Screen



Set programs



Pneumatic



- * Sports goods.
- * Advertising, flags, banners, accessories.
- * Large photos, posters.
- * Transfer on Hard Substrate (ceramic, aluminium, plastic, wood...)

- * Textile : home finishing, apparel, curtains...
- * Awning

- Ideal for sublimation with good productivity and flexibility.
- Fast startup ! (15 to 20min)
- Plate in rectified high quality aluminium
- Perfect heat distribution (Multiple heating zones)
- PT100 platinum heat sensor
- 2-year guarantee on the machine.
- 10-year guarantee on heating elements
- Front load motorized double sliding plate.
- Manufactured in France.

OPTIONAL ACCESSORIES




Sublimation paper



Polyester Felt



Nomex® Cover



Teflon Cover



Air extractor



Compressor

Email

sales@sefa.fr
support@sefa.fr
www.sefa.fr



Phone

Office : + 33 4 68 74 05 89
Fax : + 33 4 68 74 24 08



Address

SEFA SAS
Z.I. PASTABRAC
11 260 ESPERAZA (FR)



TRANSFER
YOUR IMAGINATION

Chemica

Stillscreen

Sefa

Eims

TransferID

TECHNICAL CHARACTERISTICS

Type	Pneumatic
Operation	SLIDE - Tray with drawer
Platen size	SUBLI-1510+ : 1570x1070 mm SUBLI-1812 : 1800x1200 mm SUBLI-2513 : 2550x1300 mm
Weight	SUBLI-1510+ : 1000 KG SUBLI-1812 : 1394 KG SUBLI-2513 : 2180 KG
Max thickness	45 mm
°C / °F Max	220 °C / 429 °F
Power	SUBLI-1510+ : 20,25 KW SUBLI-1812 : 30,25 KW SUBLI-2513 : 35 KW
Power supply	400 V 3-phases
Amperage	SUBLI-1510+ : 32 A SUBLI-1812 : 46 A SUBLI-2513 : 56 A
Applications	ChromaLuxe, Sublimation Rigid Substrate, Textile Sublimation

SETTINGS



Touch electronics developed by Sefa
Precise and fast regulation (PID control)
4 recordable programs
Counter with reset
Double timer
Energy saving

From 0 to 570 sec (precision +/- 1%).
From 0 to 220°C (precision +/- 1%).

Heating time to reach 180°C : 15 min.

OPTIONAL ACCESSORIES




ASP-SUBLI
Exhaust system to evacuate
sublimation fumes.



COMP-240 / COMP-300
Silent compressor 42dB(a)
COMP-240 : 50L. 240Lt/min.
for SUBLI-1510+
COMP-300 : 150L. 300Lt/min.
for SUBLI-1812



FEU-P1510 / P1812 / P2513
Polyester felt for lower plate.



TOI-T1510 / T1812 / T2513
Teflon cover for heating
plate.



TOI-N1510 / N1812 / N2513
Nomex® cover for heating
plate.



SE64300 / SE44100
High quality sublimation
paper available in 44"x30m
and 64"x100m.

DIMENSIONS


SUBLI-1510+



SUBLI-1812



SUBLI-2513



Box weight CAI-SUBLI : 327 kg
Box weight CAI-SUBLI2513 : 432 kg